

.050" SHROUDED HEADER (Straight)

FEATURES


- Four wall shielding provides unmated pin protection
- Polarizing slot assures proper mating
- Smaller centers allow for higher density packaging
- Hi Temp Plastic is IR, Vapor Phase, and Wave Solder compatible
- Mates with Crane's AFF and ATF Series sockets

STANDARD PART DIMENSIONS


MATING		Dual Row PLF	Dual Row PLH
P	POST "C"	0.120" / 3,05mm	0.120" / 3,05mm
	POST "B"	Not Available	0.220" / 5,59mm
INSULATOR BODY		Dual Row PLF	Dual Row PLH
W	WIDTH	0.245" / 6,22mm	0.295" / 7,49mm
D	DEPTH	0.160" / 4,06mm	0.245" / 6,22mm
H	HEIGHT (Add .010" for SMT)	0.215" / 5,46mm	0.300" / 7,62mm
I	INSIDE	(#Pos. X 0.025") + 0.028"	(#Pos. X 0.025") + 0.028"
O	OUTSIDE	(#Pos. X 0.025") + 0.160"	(#Pos. X 0.025") + 0.160"
C1	ROW TO ROW	0.050" / 1,27mm	0.100" / 2,54mm
PC TAIL		Dual Row PLF	Dual Row PLH
A	PAD CENTERLINE	0.050" / 1,27mm	0.050" / 1,27mm
B	SPACING	0.330" / 8,38mm	0.380" / 9,65mm
C2	PAD SIZE	0.025" / 0,64mm	0.025" / 0,64mm
E	PAD SIZE	0.100" / 2,54mm	0.100" / 2,54mm
PC TAIL LENGTH (Thru-Hole Version)		Dual Row PLF	Dual Row PLH
L	LENGTH	0.100" / 2,54mm	0.100" / 2,54mm
MATERIALS			
INSULATOR BODY		High Temperature Thermoplastic (UL94V-O)	
POST		Phosphor Bronze	

See SPECIFICATIONS and PERFORMANCE DATA for more detail


PLF THRU-HOLE (10 to 100 Positions)




PLH THRU-HOLE (10 to 100 Positions)



PLF SURFACE MOUNT (10 to 100 Positions)



PLH SURFACE MOUNT (10 to 100 Positions)



SAMPLE HOTLINE: 1-800-676-7644

0.050" (1,27mm) Centers 0.018" (0,46mm) Square Mating Posts	HOW TO ORDER CRANE'S PLF / PLH SERIES								
	STANDARD PART NUMBER							OPT.	

PRODUCT SERIES	PL								
INSULATOR STYLE	050 x 050	F							
	050 x 100	H							
TOTAL NUMBER OF POSITIONS	DUAL		10-100						
NOTE: Available only in MULTIPLES OF TEN									
NUMBER OF ROWS	DUAL			D					
TYPE OF HEADER	STRAIGHT				S				
PLATING (See Plating Specifications Below)	G or T								
MATING POST DATA	MATING POST LENGTH				MIN. GOLD PLATED AREA				
NOTE: The "B" option mating post is available on the PLH version only.	0.230" / 5,84mm				0.150" / 3,81mm				B
	0.120" / 3,05mm				0.080" / 2,03mm				C
TAIL (0.100" / 2,54mm) STANDARD	THRU-HOLE				0.018" / 0,46mm SQ				Q
TAIL	SURFACE MOUNT				N/A				S
OTHER THRU-HOLE TAIL OPTIONS	KINKED				0.018" / 0,46mm SQ				K
	COINED				0.020" / 0,51mm DIAG				R

Alignment post option available on surface mount version. Please contact factory for ordering information.

CRANE CONNECTORS - PLATING SPECIFICATIONS

PLATING OPTIONS		CONTACT AREA Inches (Millimeters)	PC TAIL Inches (Millimeters)	UNDERPLATE Inches (Millimeters)
G	Selective	15 μ in (0,00038) Gold	100 μ in (0,00254) Tin/Lead - Min.	50 μ in (0,00127) Nickel - Min.
T	Tin / Lead	100 μ in (0,00254) Tin / Lead	100 μ in (0,00254) Tin/Lead - Min.	50 μ in (0,00127) Nickel - Min.
M	Selective	50 μ in (0,00127) Gold	100 μ in (0,00254) Tin/Lead - Min.	50 μ in (0,00127) Nickel - Min.
H	Selective	30 μ in (0,00076) Gold	100 μ in (0,00254) Tin/Lead - Min.	50 μ in (0,00127) Nickel - Min.
L	Selective	10 μ in (0,00025) Gold	100 μ in (0,00254) Tin/Lead - Min.	50 μ in (0,00127) Nickel - Min.
F	Selective	3 μ in (0,00008) Gold	100 μ in (0,00254) Tin/Lead - Min.	50 μ in (0,00127) Nickel - Min.

ENGINEERING NOTE:

The information presented in this catalog page is accurate to the best of our knowledge. Due to ongoing efforts to advance design and material performance, the information is subject to change without notice.

STANDARDS

ISO9001



Crane Connectors
File No. A-3620

Registered by UL to ISO9001 under UL's accreditation by Raad voor de Certificatie (RvC), the Dutch Council for Certification.

SAMPLE HOTLINE: 1-800-676-7644

CRANE CONNECTORS • 4700 Smith Road • Cincinnati, Ohio 45212 USA • E-mail Address: info@craneconnectors.com
Phone: (513) 631-4700 • Fax (513) 631-5700 • Toll Free US (800) 676-7644 • Canada (800) 420-7310